

# PATENT ABSTRACTS OF JAPAN

(11)Publication number : **62-064132**

(43)Date of publication of application : **23.03.1987**

(51)Int.Cl. **H04B 1/16**

**H04H 1/00**

**H04N 5/00**

**H04N 7/10**

(21)Application number : **60-203717**

(71)Applicant : **MATSUSHITA ELECTRIC IND  
CO LTD**

(22)Date of filing : **13.09.1985**

(72)Inventor : **OZAKI HIROYUKI**

## (54) TELEVISION RECEIVER

### (57)Abstract:

**PURPOSE:** To eliminate the need for disconnection after an emergency alarm service station is selected at power disconnection by putting an emergent alarm channel in the channel information 1st position of a memory when channel selection information is stored in the memory.

**CONSTITUTION:** An address L storing a channel position during channel selection of memory 18 is rewritten at each channel selection by a microcomputer 17 and an address P is rewritten at each application/disconnection of a power supply. When a power key of a key matrix 13 is depressed, the computer 17 reads the content of the address P and when power is applied, a power circuit 9 is disconnected. Then a channel data of an M1 of the memory 18 is transferred to a channel selection circuit 3. Thus, when the power is disconnected and a TV receiver is in the standby, the channel of the position 1 is received without fail and in storing an alarm broadcast service station to the position 1, the emergency broadcast is received without fail by an emergency alarm broadcast reception decoder.

